



## UV BULB POWER SUPPLY WIRE

### KEY FEATURES

- UL 1371, FEP insulation, Nominal wall 0.006” (0.15mm)
- Conductor is Tin Plated Copper
- #26 19/38 TC White, Markel Part FW26W0600
- Light Sources Part MAROLOPGRW01
- 10,000 ft (3,048 m) per spool x 4 spools per box = 67 Lbs.
- #24 19/36 TC White, Markel Part FW24W0600
- Light Sources Part MAROLOPGRW02
- 5,000 ft. (1,524 m) per spool x 4 spools per box = 60 Lbs
- Plastic Spool Size: 11.75 in. (29.84 cm) x 4 in (10.6 cm)
- Spindle Hole 2 in (5.08 cm) diameter
- 4 Spools per box are loaded 8 boxes on one row per pallet.
- Pallet Size: 48 in (40.64 cm) x 42 in (30.48 cm) x 5.5 in (14 cm)
- Pallet Weight: 35 Lbs.

All materials of construction are warranted to meet specification and certified to be made from top quality resins without PFOA surfactant.

435 School Lane, Plymouth Meeting, PA 19462 Phone 610 272 8960 Fax 610 270 3138  
E-mail [sales@markelcorporation.com](mailto:sales@markelcorporation.com)  
[www.markelcorporation.com](http://www.markelcorporation.com)